



WALL

LINEAR

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC



 daltile
IMAGINE WHAT'S POSSIBLE

LINEAR

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC

A Spectacular Spectrum

The element of color is visually represented in Color Wheel™. This vibrant collection offers a wide spectrum of colorful selections from bright and pigmented hues to neutral and earthy tones. A favorite of artists and designers, Color Wheel provides the perfect palette to inspire the imagination.

- COLOR SCHEME
 - Eight rich semi-gloss colorful accents
 - Plus, eight coordinating neutral tones in semi-gloss and matte finishes
- ARTISTIC INSPIRATIONS
 - Stylish shapes in unique linear size options
 - With endless design opportunities, this collection is a perfect fit for residential and commercial applications

WALL

USAGE



FLOOR



WALL



COUNTERTOP



SHOWER FLOOR



EXTERIOR FLOOR



STEPWISE™



TRU-EDGE™



MADE IN THE U.S.A.



LARGE FORMAT



MOSAIC/DECO



ENCAUSTIC



TERRAZZO



PAVER



CUSTOMIZE



FLEXFIT™



C.G.
GLAZED CERAMIC

LOW HIGH

SPECIAL FEATURES

NOT APPLICABLE FOR ALL PRODUCTS IN THIS SERIES. SEE CHARTS FOR FULL PRODUCT DETAILS.

Cover photo features Color Wheel™ Linear Arctic White, Desert Gray & Chalkboard 6 x 18 on wall.


Above photo features Color Wheel™ Linear Matte Architectural Gray & Plum Crazy 6 x 18 on the wall.

SIZES:




FINISHES: MATTE | SEMI-GLOSS


SEMI-GLOSS




BLACK
K111 (2)



ARCTIC WHITE
0190 (1)



BISCUIT
K175 (1)



URBAN PUTTY
0161 (2)



ARCHITECTURAL
GRAY 0109 (2)



DESERT GRAY
X114 (1)




SUEDE GRAY
0182 (2)




CHALKBOARD
0180 (2)


MATTE



MATTE BLACK
K711 (2)



MATTE ARCTIC WHITE
0790 (1)



MATTE BISCUIT
K775 (1)



MATTE URBAN PUTTY
0761 (2)



MATTE ARCHITECTURAL
GRAY 0709 (2)



MATTE DESERT GRAY
X714 (1)



MATTE SUEDE GRAY
0782 (2)



MATTE CHALKBOARD
0780 (2)

ACCENT*



MUSTARD
1012 (3)



ORANGE BURST
1097 (3)



CURRANT
SH17 (3)



EMERALD
0115 (3)



SEA BREEZE
1174 (3)



OCEAN BLUE
1049 (3)



NAVY**
K189 (3)



PLUM CRAZY
1178 (3)

* Accent available in Semi-Gloss finish only.
(1), (2) and (3) indicate price groups. (1) being the least expensive.
** Subject to crazing, do not use black grout.



STAINPROOF



DENTPROOF



SCRATCH-RESISTANT*
*Applicable to products with Matte and Textured Finishes



FIRE-RESISTANT









SIMPLICLEAN™

LINEAR

COLOR WHEEL™ COLLECTION – GLAZED CERAMIC

WALL










SIZES

			Thickness	Sq. Ft./ Carton	Pieces/ Carton
	8 x 24 Wall Tile	(8" x 24") (20.34 cm x 61.03 cm)	3/8" (9.30 mm)	13.30	10
	6 x 18 Wall Tile	(6" x 18") (15.25 cm x 45.76 cm)	3/8" (9.30 mm)	11.25	15
	4 x 16 Wall Tile	(4" x 16") (10.17 cm x 40.68 cm)	3/8" (9.30 mm)	13.20	30
	4 x 12 Wall Tile	(4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16" (7.90 mm)	10.64	28
	4 x 8 Wall Tile	(4-1/4" x 8-9/16") (10.91 cm x 21.82 cm)	5/16" (7.90 mm)	10.63	42
	2 x 8 Wall Tile	(2-1/8" x 8-9/16") (5.45 cm x 21.82 cm)	5/16" (7.90 mm)	10.40	80

LRV & MUNSELL

Color #	LRV Illuminate-OBS: F02-02 (CWF)	Munsell
SEMI-GLOSS		
0190	83.9	7.0Y 9.2/0.2
K175	75.9	5.2Y 8.8/0.9
0161	48.0	1.7Y 7.3/1.5
0109	37.9	6.0Y 6.6/1.0
X114	43.7	1.4GY 7.0/0.3
0182	22.6	1.9B 5.3/0.1
0180	11.4	1.3B 3.9/0.4
K111	5.0	10.0B 2.6/0.1
MATTE		
0790	83.4	4.9Y 9.2/0.2
K775	75.9	5.2Y 8.8/0.9
0761	48.1	2.5Y 7.3/1.5
0709	36.9	5.6Y 6.5/1.0
X714	43.9	3.6GY 7.0/0.4
0782	22.3	9.8G 5.3/0.1
0780	11.1	0.6B 3.9/0.4
K711	5.8	3.3PB 2.8/0.1
ACCENT		
K189	5.9	5.0PB 2.9/1.2
1012	48.1	9.7YR 7.2/6.9
1049	18.0	1.9B 5.0/4.5
1097	26.4	10.1R 5.6/10.2
0115	12.4	3.4G 4.2/4.6
1174	9.1	5.8PB 3.6/5.6
1178	6.8	5.9RP 3.1/2.0
SH17	14.0	5.1R 4.4/11.1

TRIM

			Thickness	Pieces/ Carton
	S1/212J / 1/2 x 12 Jolly	(1/2" x 11-15/16") (1.29 cm x 30.36 cm)	1/4" (7.23 mm)	12
	S44D9 / 4 x 16 Bullnose (on 16" side)	(4" x 16") (10.17 cm x 40.68 cm)	3/8" (9.30 mm)	24
	SN44D9 / 4 x 4 Bullnose Corner	(4" x 4") (10.17 cm x 10.17 cm)	3/8" (9.30 mm)	20
	S44C9MOD / 4 x 12 Bullnose (on 12" side)	(4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16" (7.90 mm)	28
	S4489MOD / 4 x 8 Bullnose (on 8" side)	(4-1/4" x 8-9/16") (10.91 cm x 21.82 cm)	5/16" (7.90 mm)	42
	SCRL4449 / 4 x 4 Bullnose Corner	(4-1/4" x 4-1/4") (10.91 cm x 10.91 cm)	5/16" (7.90 mm)	100
	S4289MOD / 2 x 8 Bullnose (on 8" side)	(2-1/8" x 8-9/16") (5.45 cm x 21.82 cm)	5/16" (7.90 mm)	80
	SN4289M / 2 x 2 Bullnose Corner	(2-1/8" x 2-1/8") (5.45 cm x 5.45 cm)	5/16" (7.90 mm)	25
	A34CIMOD / 4 x 12 Flat Top Cove Base	(4-1/4" x 12-7/8") (10.91 cm x 32.77 cm)	5/16" (7.90 mm)	40

TRIM USAGE

Wall Tile	8x24	6x18	4x16	4x12	4x8	2x8
Jolly	S1/212J	S1/212J	S1/212J	S1/212J	S1/212J	S1/212J
Quarter Round	A106	A106	A106	A106	A106	A106
Quarter Round Corner	AC106	AC106	AC106	AC106	AC106	AC106
SURFACE BULLNOSE						
Bullnose		S44D9	S44C9MOD	S4489MOD	S4289MOD	
Corner		SN44D9	SCRL4449	SCRL4449	SN4289M	
RADIUS BULLNOSE						
Bullnose	A4200	A4200	A4200	A4200	A4200	A4200
Corner	AN4200	AN4200	AN4200	AN4200	AN4200	AN4200
FLAT TOP COVE BASE						
Cove Base	A34CIMOD	A34CIMOD	A34CIMOD	A34CIMOD	A34CIMOD	A34CIMOD
Cove Base Corner*	SCR3401 & SCL3401	SCR3401 & SCL3401	SCR3401 & SCL3401	SCR3401 & SCL3401	SCR3401 & SCL3401	SCR3401 & SCL3401

* See Color Wheel Classic product line.



APPLICATIONS

	Target DCOF wet	Suitable
Dry & Level – Interior Floor	N/A	
Wet & Level – Interior Floor	≥ 0.42	
Shower Floors (Residential or Light Commercial)	≥ 0.42	
Exterior Floor Applications (including patios, pool decking & other wet areas with minimal footwear)	≥ 0.60	
Ramps & Inclines	≥ 0.65	
Walls/Backsplashes	N/A	✓
Countertops	N/A	
Pool Linings	N/A	

A DCOF value of ≥ 0.42 is the standard for tiles specified for level interior spaces expected to be walked upon when wet, as stated in ANSI A137.1-2012, Section 9.6. For more information about DCOF and the DCOF AcuTest™, visit daltile.com/DCOF.

APPLICATION NOTES:


Suitable for exterior applications in non-freezing climates, when proper installation methods are followed.

PERFORMANCE CHARACTERISTICS

	ASTM#	Result
Water Absorption	C373	< 20.0%
Breaking Strength	C648	120-230 lbs
Scratch Hardness	MOHS	4.0-6.0
Chemical Resistance	C650	Resistant
Abrasion Resistance	C1027	N/A

For additional information on test results, visit us at: daltile.com/information/TestResults.

INSTALLATION

Grout Joint Recommendation	Shade Variation
<p>6 x 18 & 8 x 24: 1/16" (1/8" when rectangular size is installed in a staggered brick-joint pattern; overlap should not exceed 33%.)</p> <p>2 x 8, 4 x 12, & 4 x 16: 1/16" (When rectangular size is installed in a staggered brick joint pattern, overlap should not exceed 33%.)</p> <p>4 x 8: 1/16"</p>	 Low (V1)

NOTES

Since there are variations in all fired ceramic and natural products, tile and trim supplied for your particular installation may not match samples. Final confirmation should be made from actual tiles and trim prior to installation. Manufactured in accordance with ANSI A137.1 standards.

For additional information refer to "Factors to Consider" at: daltile.com/Factors.



POST-CONSUMER RECYCLED MATERIALS



PRE-CONSUMER RECYCLED MATERIALS

All or select items within this series meet the requirements for these qualifications. For more information, visit daltile.com.



LEARN MORE

7834 C.F. Hawn Freeway,
Dallas, Texas 75217 | 1.800.933.TILE

To view the complete collection of Daltile® products and information, visit our website at daltile.com.



IMAGINE WHAT'S POSSIBLE™

©2022 Daltile (1/22)