# **KPF-3125**

# Industrial Bridge Kitchen Faucet



# **Faucet Dimensions**

Overall Height: 11 3/8" - 12 3/8" \*adjustable Spout Height: 8 3/8" - 9 3/8" \*adjustable Spout Reach: 9 3/4"

#### **Features**

- Bridge Faucet
- Brass Construction
- Lead Free Brass Waterway
- 360° Swivel Spout
- Flow Rate: 1.8 gpm (6.8L/min) @ 60 psi
- 3 or 4 Hole Installation
- Stream Function with Optional Side Sprayer
- Quarter Turn Ceramic Disk Cartridge
- 24" Integrated Nylon Waterlines
- Dome Shaped Screen Washer
- Quick Connect Sprayer Hose
- 13 3/4" Hose Length
- Connections 3/8" Compression
- Max Deck Thickness: 2 1/2"
- TPI of aerator in the Sprayer M22 x 1

# **Available Finishes**

- Spot Free Stainless Steel
- Matte Black
- Matte Black/Red
- Brushed Gold
- · Matte Black/Grey Color Changing

# **CODES/STANDARDS:**

# **Product Certification**


cUPC (ASME A112.18.1/CSA B125.1) NSF/ANSI Standard 61 and 372 certified by IAPMO CAL GREEN, CEC, DOE


**NOTE:** Some Kitchen Faucets that do not have a pull out or pull down sprayer may be connected to a portable dishwasher. Pull out and pull down faucets should never be connected to portable dishwashers because potential pressure fluctuations during washing cycles cause hose ruptures or leaks.

# Warranty

Kraus Limited Lifetime Warranty see website for details www.kraususa.com







# FF-101

# Industrial Drinking Water Filtration Faucet



# **Faucet Dimensions**

Overall Height: 11" Spout Height: 9 3/8" Spout Reach: 5 3/8"

#### **Features**

- Filter Faucet
- Brass Construction
- Lead Free Brass Waterway
- Flow Rate: 1.0 gpm (3.79L/min) @ 60 psi
- Stream Function
- Quarter Turn Ceramic Disk Cartridge
- 3/8" Push In Water Supply Connection
- Max Deck Thickness: 3 1/16"
- Fits Most Under-Counter Drinking Water Systems

#### **Accessories Included**

- Hex Wrench
- 1/4" Push In Water Supply Connection

# **Available Finishes**

- Spot Free Stainless Steel
- Matte Black
- Brushed Gold
- Matte Black/Red

# **CODES/STANDARDS:**

### **Product Certification**

cUPC (ASME A112.18.1/CSA B125.1) NSF/ANSI Standard 61 and 372 certified by IAPMO CAL GREEN, CEC, DOE

**NOTE**: Some Kitchen Faucets that do not have a pull out or pull down sprayer may be connected to a portable dishwasher. Pull out and pull down faucets should never be connected to portable dishwashers because potential pressure fluctuations during washing cycles cause hose ruptures or leaks.

### Warranty

Kraus Limited Lifetime Warranty see website for details www.kraususa.com



